

# Standard Display 32" FHD (S32A)

**SOLUM**  
Signage

## Model information

- Modelname: S32A
- Modelcode: WC32FAFSAE0HSM
- Series: S Series
- EAN: 8809580802569

## Display

- Resolution: 1,920(H) x 1,080(V)
- Back Light Type: Edge LED
- Luminance: 500 cd/m<sup>2</sup>
- Contrast: 4000:1

## Design/Connectivity

- Connectivity: 2 x USB 2.0 Type A, 1 x RS232C, 3 x HDMI
- Bezel Width: 11.6 mm(U/L/R/B)

## Other feature

- FHD Signage Display
- Android OS 9.0
- 24/7

Front



Back



Side



Port



# Standard Display 32" FHD (S32A) Specification

## Article information

|            |                |
|------------|----------------|
| Model Name | S32A           |
| Model Code | WC32FAFSAE0HSM |
| EAN        | 8809580802569  |

## Display

|                     |                         |
|---------------------|-------------------------|
| Size                | 32"                     |
| Resolution          | 1,920(H) x 1,080(V)     |
| WXH Ratio           | 1,77 (16:9)             |
| Luminance           | 500 cd/m <sup>2</sup>   |
| Portrait Mode       | Support                 |
| Contrast Ratio      | 4000:1                  |
| Viewing Angle (H/V) | 178° / 178°             |
| Response Time       | 8 ms                    |
| Active Area         | 698,4(H) x 392,85(V) mm |
| Color Gamut         | 85%                     |
| Back Light type     | E-LED                   |
| Life Time (LED)     | 50,000 Hrs              |
| Operating Time      | 24/7                    |

## System

|              |                                 |
|--------------|---------------------------------|
| OS           | Android 9.0                     |
| CPU          | T963, Quad-core ARM Cortex-A35  |
| GPU          | ARM Mali-G31 MP2                |
| RAM          | 2GB DDR4                        |
| Storage      | 8GB eMMC                        |
| Network      | Ethernet (RJ45) Wi-Fi (2,4G/5G) |
| Connectivity | USB 2.0 Type A 2EA, RS232C      |
| HDMI / DP    | HDMI 3ea                        |
| Speaker      | 10W + 10W                       |
| Touch        | No                              |

## Power Requirements

|                   |                       |
|-------------------|-----------------------|
| Power Consumption | 70W(Typ)              |
| Standby Power     | ≤ 0.5W                |
| Power Resource    | AC 110 ~240V @50/60Hz |

## Mechanical

|                           |                           |
|---------------------------|---------------------------|
| SET Outline Dimension     | 724.6 x 419.8 x 40 mm     |
| VESA                      | 150 x 200 mm              |
| SET Weight                | 5.4kg                     |
| Packing Outline Dimension | 795 x 520 x 115 mm        |
| Packing Weight            | 7.3kg                     |
| Bezel Width (U/L/R/D mm)  | 11.6 / 11.6 / 11.6 / 11.6 |

## Environmental

|                       |            |
|-----------------------|------------|
| Operation Temperature | 0 ~ 40°C   |
| Operation Humidity    | 20% - 80%  |
| Storage Temperature   | -20 ~ 60°C |
| Warranty              | 3 Years    |

\* All specifications are subject to change without notice.  
Errors and omissions are excepted. August. 2024